

Product: Aromax 150

Technical Data Sheet

Property	Unit	Specification	Test Method
Appearance		Bright and Clear	Visual
Specific Gravity (15 °C)		0.881 - 0.905	ASTM D4052
Saybolt Color		Min 28	ASTM D156
Distillation - IBP - DP	°C	Min 175 Max 216	ASTM D850
Aromatics	Wt %	Min 98	ASTM D6563
Mixed Aniline Point	°C	Max 18	ASTM D611
Flash Point	°C	Min 62	ASTM D93
Copper Corrosion		Max 1	ASTM D130
Water Content	ppm	Max 200	ASTM D1744
Cloud Point	°C	Max -10	ASTM D2500
Total Sulfur	ppm	Max 10	ASTM D5453
t-Naphthalene	Vol %	As reported	ASTM D6563

Description

Aromax 150, consisting mainly of C10 hydrocarbon is a clear colourless liquid, with a distinct aromatic odour. It is sparingly soluble in water but immiscible with alcohols and most organic solvents.

Coatings and Inks

As solvents in nitrocellulose lacquers, varnishes, paints, enamels due to its high solvency power. Aromax 150 is also used to manufacture adhesives and printing inks.

Insecticides and Herbicides

As components in the liquid formulation of insecticides and herbicides due to its high solvency power and relatively high flash point.

Other Applications

Used as a component in gasoline and as a general cleaning agent.

Revision Date: 23 April 2024
